

## Safety Data Sheet

## Firestone Building Products Company

**Section 1: Identification of the Substance/Mixture and of the Company/Undertaking****1.1 Product identifier****Product Name** | **FillGard™ M Pourable Sealer Part A****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified use(s)** | Construction**1.3 Details of the supplier of the safety data sheet****Manufacturer** | Firestone Building Products Company250 West 96th Street  
Indianapolis, IN 46260  
United States

firestonemsds@bfdp.com

**Telephone (General)** | 800-428-4442**1.4 Emergency telephone number****Manufacturer** | (800) 424-9300 - CHEMTREC**Manufacturer** | (703) 527-3887 - CHEMTREC - International**Section 2: Hazards Identification****EU/EEC**

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

**2.1 Classification of the substance or mixture**

<b>CLP</b>	Skin Irritation 2 - H315 Skin Sensitization 1 - H317 Eye Irritation 2 - H319 Acute Toxicity Inhalation 4 - H332 Respiratory Sensitization 1 - H334 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335 Carcinogenicity 2 - H351 Specific Target Organ Toxicity Repeated Exposure 2 - H373
<b>DSD/DPD</b>	Harmful (Xn) Irritant (Xi) Carcinogenic Substances - Category 3 R20, R36/37/38, R40, R42/43, R48/20

**2.2 Label Elements****CLP****DANGER**



**Hazard statements** | H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.

## Precautionary statements

**Prevention** | P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P260 - Do not breathe mist/vapours/spray.  
P264 - Wash thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves, clothing, and eye/face protection, .  
P281 - Use personal protective equipment as required.  
P285 - In case of inadequate ventilation wear respiratory protection.

**Response** | P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
P321 - Specific treatment, see supplemental first aid information.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P314 - Get medical advice/attention if you feel unwell.

**Storage/Disposal** | P403+P233 - Store in a well-ventilated place. Keep container tightly closed. Keep away from moisture.  
P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Supplemental information** | 59 percent of this product consists of an ingredient of unknown toxicity.  
**DSD/DPD**



**Risk phrases** | R20 - Harmful by inhalation.  
R36/37/38 - Irritating to eyes, respiratory system and skin.  
R40 - Limited evidence of a carcinogenic effect.  
R42/43 - May cause sensitisation by inhalation and skin contact.  
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**Safety phrases** | S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36 - Wear suitable protective clothing.  
S37 - Wear suitable gloves.  
S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
S53 - Avoid exposure - obtain special instructions before use.

## 2.3 Other Hazards

**CLP** | According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

## DSD/DPD

According to European Directive 1999/45/EC this preparation is considered dangerous.

## United States (US)

According to OSHA 29 CFR 1910.1200 HCS

### 2.1 Classification of the substance or mixture

#### OSHA HCS 2012

Skin Irritation 2 - H315  
 Skin Sensitization 1A - H317  
 Eye Irritation 2 - H319  
 Respiratory Sensitization 1A - H334  
 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335  
 Specific Target Organ Toxicity Repeated Exposure 1 - H372

### 2.2 Label elements

#### OSHA HCS 2012

## DANGER



#### Hazard statements

Causes skin irritation - H315  
 May cause an allergic skin reaction - H317  
 Causes serious eye irritation - H319  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled - H334  
 May cause respiratory irritation - H335  
 Causes damage to organs through prolonged or repeated exposure. - H372

#### Precautionary statements

##### Prevention

Do not breathe mist/vapours/spray. - P260  
 Wash thoroughly after handling. - P264  
 Do not eat, drink or smoke when using this product. - P270  
 Use only outdoors or in a well-ventilated area. - P271  
 Contaminated work clothing should not be allowed out of the workplace. - P272  
 Wear protective gloves, clothing, and eye/face protection, . - P280  
 In case of inadequate ventilation wear respiratory protection. - P285

##### Response

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340  
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. - P342+P311  
 If on skin: Wash with plenty of water. .  
 Specific treatment, see supplemental first aid information. - P321  
 If skin irritation or rash occurs: Get medical advice/attention. - P333+P313  
 Take off contaminated clothing and wash before reuse. - P362  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - P305+P351+P338  
 If eye irritation persists: Get medical advice/attention. - P337+P313  
 Get medical advice/attention if you feel unwell. - P314

##### Storage/Disposal

Store in a well-ventilated place. Keep container tightly closed. - P403+P233  
 Keep away from moisture.  
 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501

### 2.3 Other hazards

#### OSHA HCS 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

## Canada

According to WHMIS

## 2.1 Classification of the substance or mixture

### WHMIS

- | Very Toxic - D1A
- | Other Toxic Effects - D2A
- | Other Toxic Effects - D2B

## 2.2 Label elements

### WHMIS



- | Very Toxic - D1A
- | Other Toxic Effects - D2A
- | Other Toxic Effects - D2B

## 2.3 Other hazards

### WHMIS

- | In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

## Section 3 - Composition/Information on Ingredients

### 3.1 Substances

- | Material does not meet the criteria of a substance.

### 3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Isocyanic acid, methylenedi-p-phenylene ester	<b>CAS:</b> 101-68-8 <b>EC Number:</b> 202-966-0 <b>EU Index:</b> 615-005-00-9	20% TO 40%	Ingestion/Oral-Rat LD50 • 9200 mg/kg Inhalation-Rat LC50 • 178 mg/m <sup>3</sup>	<b>EU DSD/DPD:</b> Annex VI, Table 3.2: Carc. Cat. 3; R40; Xn R20-48/20; Xi R36/37/38 R42/43 <b>EU CLP:</b> Annex VI, Table 3.1: Carc. 2, H351; Acute Tox. 4, H332; STOT RE 2, H373; Eye Irrit. 2, H319; Skin Irrit. 2, H315; STOT SE 3, H335; Resp. Sens. 1, H334; Skin Sens. 1, H317 <b>OSHA HCS 2012:</b> Eye Irrit. 2; Skin Irrit. 2; Skin Sens. 1A; STOT SE 3: Resp. Irrit.; Resp. Sens. 1A; STOT RE 1 (Lungs);	NDA
Siloxanes and Silicones, di-Me, reaction products with silica	<b>CAS:</b> 67762-90-7	1% TO 5%	NDA	<b>EU DSD/DPD:</b> Not Classified <b>EU CLP:</b> Not Classified <b>OSHA HCS 2012:</b> Not Classified	NDA
Propane, 1,2-epoxy-	<b>CAS:</b> 75-56-9 <b>EC Number:</b> 200-879-2 <b>EU Index:</b> 603-055-00-4	< 0.1%	Ingestion/Oral-Rat LD50 • 380 mg/kg Inhalation-Rat LC50 • 4000 ppm 4 Hour(s) Skin-Rabbit LD50 • 1500 µL/kg	<b>EU CLP:</b> Community workplace exposure limit <b>OSHA HCS 2012:</b> Exposure limits	NDA
Furan	<b>CAS:</b> 110-00-9 <b>EC Number:</b> 203-727-3	< 0.1%	NDA	<b>EU CLP:</b> Community workplace exposure limit <b>OSHA HCS 2012:</b> Exposure limits	NDA

	EU Index:603-105-00-5				
Cobalt	CAS:7440-48-4 EC Number:231-158-0 EU Index:027-001-00-9	< 0.1%	Ingestion/Oral-Rat LD50 • 6171 mg/kg	EU CLP: Community workplace exposure limit OSHA HCS 2012: Exposure limits	NDA
Acetaldehyde	CAS:75-07-0 EC Number:200-836-8 EU Index:605-003-00-6	< 0.1%	Ingestion/Oral-Rat LD50 • 661 mg/kg Inhalation-Rat LC50 • 13300 ppm 4 Hour(s) Skin-Rabbit LD50 • 3540 mg/kg	EU CLP: Community workplace exposure limit OSHA HCS 2012: Exposure limits	NDA

## Section 4 - First Aid Measures

### 4.1 Description of first aid measures

#### Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately.

#### Skin

- Remove contaminated clothing and shoes. Wash immediately with soap and water for at least 15 minutes. Discard contaminated shoes and clothing. If irritation develops and persists, get medical attention.

#### Eye

- Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. If eye irritation persists: Get medical advice/attention.

#### Ingestion

- Get medical attention if symptoms occur.

### 4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

## Section 5 - Firefighting Measures

### 5.1 Extinguishing media

**Suitable Extinguishing Media** | Carbon Dioxide, Dry Chemical, Foam.

**Unsuitable Extinguishing Media** | Do not use water.

### 5.2 Special hazards arising from the substance or mixture

**Unusual Fire and Explosion Hazards** | Reacts with water and emits carbon dioxide gas. Exposure to water will initiate reaction, which may be violent.  
The product is not flammable. However, it will burn if strongly heated and when involved in fire.

**Hazardous Combustion Products** | Carbon oxides. Nitrogen oxides. Hydrocarbons. Isocyanates.

### 5.3 Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is

possible.

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

## Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### Personal Precautions

- Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

#### Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stay upwind. Keep out of low areas. Keep unauthorized personnel away. Ventilate closed spaces before entering.

### 6.2 Environmental precautions

- Avoid release to the environment.

### 6.3 Methods and material for containment and cleaning up

#### Containment/Clean-up Measures

- Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of spill for later disposal. Never return spills in original containers for re-use.

### 6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

## Section 7 - Handling and Storage

### 7.1 Precautions for safe handling

#### Handling

- Use only in well ventilated areas. Use good safety and industrial hygiene practices. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist/vapours/spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

- Keep container tightly closed. Store in a cool, dry, well-ventilated place. Keep away from incompatible materials.

### 7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

## Section 8 - Exposure Controls/Personal Protection

### 8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Alberta	Canada British Columbia	Canada Manitoba	Canada New Brunswick
Acetaldehyde (75-07-0)	Ceilings	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m3 Ceiling	25 ppm Ceiling	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m3 Ceiling
Propane, 1,2-epoxy- (75-56-9)	TWAs	2 ppm TWA	2 ppm TWA; 4.7 mg/m3 TWA	2 ppm TWA	2 ppm TWA	20 ppm TWA; 48 mg/m3 TWA

Cobalt (7440-48-4)	TWAs	0.02 mg/m3 TWA	0.02 mg/m3 TWA	0.02 mg/m3 TWA	0.02 mg/m3 TWA	0.02 mg/m3 TWA
Isocyanic acid, methylenedi-p-phenylene ester (101-68-8)	TWAs	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA; 0.05 mg/m3 TWA	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate); 0.051 mg/m3 TWA (listed under Methylene bisphenyl isocyanate)
	Ceilings	Not established	Not established	0.01 ppm Ceiling (listed under Methylene bisphenyl isocyanate (MDI))	Not established	Not established
<b>Exposure Limits/Guidelines (Con't.)</b>						
	<b>Result</b>	<b>Canada Northwest Territories</b>	<b>Canada Nova Scotia</b>	<b>Canada Nunavut</b>	<b>Canada Ontario</b>	<b>Canada Quebec</b>
Acetaldehyde (75-07-0)	STELs	150 ppm STEL; 270 mg/m3 STEL	Not established	150 ppm STEL; 270 mg/m3 STEL	Not established	Not established
	TWAs	100 ppm TWA; 180 mg/m3 TWA	Not established	100 ppm TWA; 180 mg/m3 TWA	Not established	Not established
	Ceilings	Not established	25 ppm Ceiling	Not established	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m3 Ceiling
Propane, 1,2-epoxy- (75-56-9)	STELs	30 ppm STEL; 71 mg/m3 STEL	Not established	30 ppm STEL; 71 mg/m3 STEL	Not established	Not established
	TWAs	20 ppm TWA; 47 mg/m3 TWA	2 ppm TWA	20 ppm TWA; 47 mg/m3 TWA	2 ppm TWA	20 ppm TWA/EV; 48 mg/m3 TWA/EV
Cobalt (7440-48-4)	STELs	0.3 mg/m3 STEL (dust and fume)	Not established	0.3 mg/m3 STEL (dust and fume)	Not established	Not established
	TWAs	0.1 mg/m3 TWA (dust and fume)	0.02 mg/m3 TWA	0.1 mg/m3 TWA (metal, dust and fume)	0.02 mg/m3 TWA	0.02 mg/m3 TWA/EV
Isocyanic acid, methylenedi-p-phenylene ester (101-68-8)	TWAs	Not established	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	Not established	0.005 ppm TWA (designated substances regulation, listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI))); 0.005 ppm TWA (applies to workplaces to which the designated substances regulation does not apply, listed under Methylene bisphenyl isocyanate (MDI))	0.005 ppm TWA/EV; 0.051 mg/m3 TWA/EV
	Ceilings	Not established	Not established	Not established	0.02 ppm Ceiling (designated substances regulation, listed under Isocyanates, organic compounds)	Not established

				(Methylene bisphenyl isocyanate (MDI)))	
Exposure Limits/Guidelines (Con't.)					
	Result	Canada Saskatchewan	Canada Yukon	NIOSH	OSHA
Acetaldehyde (75-07-0)	STELs	Not established	150 ppm STEL; 270 mg/m3 STEL	Not established	Not established
	TWAs	Not established	100 ppm TWA; 180 mg/m3 TWA	Not established	200 ppm TWA; 360 mg/m3 TWA
Propane, 1,2-epoxy- (75-56-9)	TWAs	2 ppm TWA	100 ppm TWA; 240 mg/m3 TWA	Not established	100 ppm TWA; 240 mg/m3 TWA
	STELs	Not established	150 ppm STEL; 360 mg/m3 STEL	Not established	Not established
Cobalt (7440-48-4)	TWAs	0.02 mg/m3 TWA	0.05 mg/m3 TWA (dust and fume)	0.05 mg/m3 TWA (dust and fume)	0.1 mg/m3 TWA (dust and fume)
	STELs	Not established	0.15 mg/m3 STEL (dust and fume)	Not established	Not established
Isocyanic acid, methylenedi-p-phenylene ester (101-68-8)	TWAs	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	Not established	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate); 0.05 mg/m3 TWA	Not established
	Ceilings	Not established	0.02 ppm Ceiling (Methylene bisphenyl isocyanate (MDI)); 0.2 mg/m3 Ceiling (Methylene bisphenyl isocyanate (MDI))	0.020 ppm Ceiling (10 min); 0.2 mg/m3 Ceiling (10 min)	0.02 ppm Ceiling; 0.2 mg/m3 Ceiling

## Exposure Control Notations

### Canada Ontario

•Isocyanic acid, methylenedi-p-phenylene ester (101-68-8): **Designated Substances:** (0.005 ppm TWA (listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI))); 0.02 ppm Ceiling (listed under Isocyanates, organic compounds (Methylene bisphenyl isocyanate (MDI))))

### Canada Quebec

- Acetaldehyde (75-07-0): **Carcinogens:** (C3 carcinogen - effect detected in animals)
- Cobalt (7440-48-4): **Carcinogens:** (C3 carcinogen - effect detected in animals)
- Propane, 1,2-epoxy- (75-56-9): **Carcinogens:** (C2 carcinogen - effect suspected in humans)

### ACGIH

- Acetaldehyde (75-07-0): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)
- Cobalt (7440-48-4): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)
- Propane, 1,2-epoxy- (75-56-9): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans) | **Sensitizers:** (Sensitizer)

## Exposure Limits Supplemental

### ACGIH

- Isocyanic acid, methylenedi-p-phenylene ester (101-68-8): **TLV Basis - Critical Effects:** (respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI)))
- Acetaldehyde (75-07-0): **TLV Basis - Critical Effects:** (eye and upper respiratory tract irritation) | **Notice of Intended Changes (TLVs):** (25 ppm Ceiling; A2 - suspected human carcinogen; TLV basis: eye and upper respiratory tract irritation)
- Cobalt (7440-48-4): **BEIs:** (15 µg/L Medium: urine Time: end of shift at end of workweek Parameter: Cobalt (background); 1 µg/L Medium: blood Time: end of shift at end of workweek Parameter: Cobalt (background, semi-quantitative)) | **TLV Basis - Critical Effects:** (asthma; myocardial effects; pulmonary function)
- Propane, 1,2-epoxy- (75-56-9): **TLV Basis - Critical Effects:** (eye and upper respiratory tract irritation) | **Notice of Intended Changes (TLVs):** (Proposed update of SEN notation to DSEN to indicate dermal sensitizer)



## 8.2 Exposure controls

### Engineering Measures/Controls

- | This material is designed to be used outdoors, in roofing applications. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

### Personal Protective Equipment

#### Respiratory

- | In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

#### Eye/Face

- | Wear safety goggles. Use face shield in case of splash risk.

#### Skin/Body

- | Wear chemical-resistant gloves, footwear and protective clothing appropriate for risk of exposure.

### Environmental Exposure Controls

- | In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

#### Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

BEI = Biological Exposure Indices

MSHA = Mine Safety and Health Administration

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TLV = Threshold Limit Value determined by the American Conference of Governmental Industrial Hygienists (ACGIH)

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

## Section 9 - Physical and Chemical Properties

### 9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Tan viscous liquid with faint aromatic odor.
Color	Tan	Odor	Faint Aromatic.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	Data lacking	Melting Point	Not relevant
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	1.1 Water=1	Water Solubility	Exposure to water will initiate reaction, which may be violent.
Viscosity	6700 Centipoise (cPs, cP) or mPas @ 75 F(23.8889 C)	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking	Volatiles (Wt.)	< 0.15 %
Volatiles (Vol.)	< 0.15 %		
Flammability			
Flash Point	> 199.4 F(> 93 C) PMCC (Pensky-Martins Closed Cup)	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking

Flammability (solid, gas)	Data lacking		
<b>Environmental</b>			
Octanol/Water Partition coefficient	Data lacking		

## 9.2 Other Information

- No additional physical and chemical parameters noted.

## Section 10: Stability and Reactivity

### 10.1 Reactivity

- Exposure to water will initiate reaction, which may be violent. CO<sub>2</sub> gas is produced.

### 10.2 Chemical stability

- Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

### 10.4 Conditions to avoid

- Keep away from heat, sparks and flame.

### 10.5 Incompatible materials

- Water. Alcohol. Alkaline metals. Acids. Bases.

### 10.6 Hazardous decomposition products

- None known.

## Section 11 - Toxicological Information

### 11.1 Information on toxicological effects

Components		
Isocyanic acid, methylenedi-p-phenylene ester (20% TO 40%)	101-68-8	<b>Acute Toxicity:</b> Ingestion-Oral-Rat LD50 • 9200 mg/kg; <b>Behavioral:Somnolence (general depressed activity); Behavioral:Ataxia; Nutritional and Gross Metabolic:Changes in Chemistry or Temperature:Body temperature decrease;</b> Inhalation-Rat TCLo • 2.4 mg/m <sup>3</sup> 6 Hour(s); <b>Lungs, Thorax, or Respiration:Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration:Other changes; Biochemical:Metabolism (intermediary):Other proteins;</b> <b>Irritation:</b> Eye-Rabbit • 100 mg • Moderate irritation; Skin-Rabbit • 500 mg 24 Hour(s)
Siloxanes and Silicones, di-Me, reaction products with silica (1% TO 5%)	67762-90-7	<b>Multi-dose Toxicity:</b> Inhalation-Rat TCLo • 30 mg/kg 6 Hour(s) 4 Week(s)-Intermittent; <b>Lungs, Thorax, or Respiration:Other changes; Blood:Hemorrhage; Related to Chronic Data:Death in the Other Multiple Dose data type field</b>

GHS Properties	Classification
Acute toxicity	EU/CLP • Acute Toxicity - Inhalation 4 - ATEmix(inhl) = 1.537 mg/L OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP • Carcinogenicity 2 OSHA HCS 2012 • Data lacking

<b>Germ Cell Mutagenicity</b>	<b>EU/CLP</b> • Data lacking <b>OSHA HCS 2012</b> • Data lacking
<b>Skin corrosion/Irritation</b>	<b>EU/CLP</b> • Skin Irritation 2 <b>OSHA HCS 2012</b> • Skin Irritation 2
<b>Skin sensitization</b>	<b>EU/CLP</b> • Skin Sensitizer 1 <b>OSHA HCS 2012</b> • Skin Sensitizer 1A
<b>STOT-RE</b>	<b>EU/CLP</b> • Specific Target Organ Toxicity Repeated Exposure 2 <b>OSHA HCS 2012</b> • Specific Target Organ Toxicity Repeated Exposure 1
<b>STOT-SE</b>	<b>EU/CLP</b> • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation <b>OSHA HCS 2012</b> • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
<b>Toxicity for Reproduction</b>	<b>EU/CLP</b> • Data lacking <b>OSHA HCS 2012</b> • Data lacking
<b>Respiratory sensitization</b>	<b>EU/CLP</b> • Respiratory Sensitizer 1 <b>OSHA HCS 2012</b> • Respiratory Sensitizer 1A
<b>Serious eye damage/Irritation</b>	<b>EU/CLP</b> • Eye Irritation 2 <b>OSHA HCS 2012</b> • Eye Irritation 2

## Potential Health Effects

### Inhalation

- Acute (Immediate)** | Harmful if inhaled. May cause respiratory irritation.
- Chronic (Delayed)** | Vapors can induce respiratory allergic sensitization with asthma-like symptoms. Symptoms include chronic cough, tightness of chest with difficulty in breathing. These symptoms may be immediate or delayed up to several hours after exposure.

### Skin

- Acute (Immediate)** | Causes skin irritation. May cause skin sensitization. Symptoms include redness, and skin rash.
- Chronic (Delayed)** | No data available

### Eye

- Acute (Immediate)** | Causes serious eye irritation.
- Chronic (Delayed)** | No data available.

### Ingestion

- Acute (Immediate)** | Ingestion may cause vomiting, nausea, diarrhea, or other systemic effects.
- Chronic (Delayed)** | No data available.

### Other

- Chronic (Delayed)** | Long-term effect of Isocyanic acid, methylenedi-p-phenylene ester on the respiratory system of 318 workers suggests that such workers may develop fibrosis. Long-term exposure tends to restrict pulmonary function and cause decrease in CO single breath transfer factor.

- Carcinogenic Effects** | Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects			
	CAS	IARC	NTP
Acetaldehyde	75-07-0	Group 1-Carcinogenic	Reasonably Anticipated to be Human Carcinogen
Cobalt	7440-48-4	Group 2B-Possible Carcinogen	Not Listed
Furan	110-00-9	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen
Propane, 1,2-epoxy-	75-56-9	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen

### Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

## Section 12 - Ecological Information

### 12.1 Toxicity

FillGard™ M Pourable Sealer Part A					
Dosage	Species	Duration	Results	Exposure Conditions	Comments
11 mg/L	<b>Algae:</b> NDA	96 Hour(s)	EC50	NDA	Ethylenediamine, N-(3-(trimethoxysilyl)propyl)-
90 mg/L	<b>Crustacea:</b> Daphnia	48 Hour(s)	EC50	NDA	Ethylenediamine, N-(3-(trimethoxysilyl)propyl)-
200 mg/L	<b>Fish:</b> NDA	96 Hour(s)	LC50	NDA	Ethylenediamine, N-(3-(trimethoxysilyl)propyl)-
>100 mg/L	<b>Crustacea:</b> Daphnia	24 Hour(s)	EC50	NDA	2(2-Hydroxy-3,5-diteramylphenyl) benzotriazole
>10 mg/L	<b>Algae:</b> NDA	72 Hour(s)	IC50	NDA	2(2-Hydroxy-3,5-diteramylphenyl) benzotriazole
>100 mg/L	<b>Fish:</b> NDA	96 Hour(s)	LC50	NDA	2(2-Hydroxy-3,5-diteramylphenyl) benzotriazole
20 mg/L	<b>Crustacea:</b> Daphnia	24 Hour(s)	EC50	NDA	Bis(1-2,2,5,6-pentamethyl-4-piperdiny)decanoate
>100 mg/L	<b>Other:</b> Bacteria	3 Hour(s)	EC50	NDA	Bis(1-2,2,5,6-pentamethyl-4-piperdiny)decanoate
0.97 mg/L	<b>Fish:</b> NDA	96 Hour(s)	LC50	NDA	Bis(1-2,2,5,6-pentamethyl-4-piperdiny)decanoate

- The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### 12.2 Persistence and degradability

- Expected to be persistent.

### 12.3 Bioaccumulative potential

- Not expected to bioaccumulate.

### 12.4 Mobility in Soil

- Water reactive material.

### 12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

### 12.6 Other adverse effects

- No studies have been found.

## Section 13 - Disposal Considerations

### 13.1 Waste treatment methods

- Product waste** | Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
- Packaging waste** | Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
----------------	------------------------------	---------------------------------	--------------------	----------------------------

<b>DOT</b>	NDA	Not Regulated	NDA	NDA	NDA
<b>TDG</b>	NDA	Not Regulated	NDA	NDA	NDA
<b>IMO/IMDG</b>	NDA	Not Regulated	NDA	NDA	NDA
<b>ADN</b>	NDA	Not Regulated	NDA	NDA	NDA
<b>ADR/RID</b>	NDA	Not Regulated	NDA	NDA	NDA
<b>IATA/ICAO</b>	NDA	Not Regulated	NDA	NDA	NDA

**14.6 Special precautions for user** | None specified.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** | Data lacking.

## Section 15 - Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** | Acute, Chronic

State Right To Know				
Component	CAS	MA	NJ	PA
Acetaldehyde	75-07-0	Yes	Yes	Yes
Cobalt	7440-48-4	Yes	Yes	Yes
Furan	110-00-9	Yes	Yes	Yes
Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	No	No	Yes
Propane, 1,2-epoxy-	75-56-9	Yes	Yes	Yes
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	No	No	No

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Acetaldehyde	75-07-0	Yes	No	Yes	No	Yes
Cobalt	7440-48-4	Yes	No	Yes	No	Yes
Furan	110-00-9	Yes	No	Yes	No	Yes
Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Yes	No	Yes	No	Yes
Propane, 1,2-epoxy-	75-56-9	Yes	No	Yes	No	Yes
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Yes	No	No	No	Yes

## Canada

### Labor

#### Canada - WHMIS - Classifications of Substances

• Propane, 1,2-epoxy-	75-56-9	B2, D1B, D2A, D2B
• Furan	110-00-9	B2, D1A, D2A
• Acetaldehyde	75-07-0	B2, D2A
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	D1A, D2A, D2B
• Cobalt	7440-48-4	D2A, D2B
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

#### Canada - WHMIS - Ingredient Disclosure List

• Propane, 1,2-epoxy-	75-56-9	1 %
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	1 %
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	0.1 %
• Cobalt	7440-48-4	0.1 %
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

### Environment

#### Canada - CEPA - Priority Substances List

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Priority Substance List 2 (substance considered toxic)
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

## Europe

### Other

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

• Propane, 1,2-epoxy-	75-56-9	F+; R12 Xn; R20/21/22 Xi; R36/37/38 Carc.Cat.2; R45 Muta.Cat.2; R46
• Furan	110-00-9	F+; R12 R19 Xn; R20/22-48/22 Xi; R38 Carc.Cat.2; R45 R52- 53 Muta.Cat.3; R68
• Acetaldehyde	75-07-0	F+; R12 Xi; R36/37 Carc.Cat.3; R40
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Xn; R20-48/20 Xi; R36/37/38 Carc.Cat.3; R40 R42/43
• Cobalt	7440-48-4	R42/43 R53
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	5%≤C: Xi; R:36/37/38 0.1% ≤C: R:42
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

• Propane, 1,2-epoxy-	75-56-9	F+ T R:45-46-12-20/21/22-36/37/38 S:53-45
• Furan	110-00-9	F+ T R:45-12-19-20/22-38-48/22-68-52/53 S:53-45-61
• Acetaldehyde	75-07-0	F+ Xn R:12-36/37-40 S:(2)-16-33-36/37
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Xn R:20-36/37/38-40-42/43-48/20 S:(1/2)-23-36/37-45
• Cobalt	7440-48-4	Xn R:42/43-53 S:(2)-22-24-37-61
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations**

• Propane, 1,2-epoxy-	75-56-9	E
• Furan	110-00-9	E
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	C, 2
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases**

• Propane, 1,2-epoxy-	75-56-9	S:53-45
• Furan	110-00-9	S:53-45-61
• Acetaldehyde	75-07-0	S:(2)-16-33-36/37
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	S:(1/2)-23-36/37-45
• Cobalt	7440-48-4	S:(2)-22-24-37-61
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**United States****Labor****U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	500 lb TQ
• Acetaldehyde	75-07-0	2500 lb TQ
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - OSHA - Specifically Regulated Chemicals**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**Environment****U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Propane, 1,2-epoxy-	75-56-9	
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	(listed under Methylene diphenyl diisocyanate)
• Cobalt	7440-48-4	Not Listed

• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed
---	------------	------------

**U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities**

• Propane, 1,2-epoxy-	75-56-9	100 lb final RQ; 45.4 kg final RQ
• Furan	110-00-9	100 lb final RQ; 45.4 kg final RQ
• Acetaldehyde	75-07-0	1000 lb final RQ; 454 kg final RQ
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	5000 lb final RQ; 2270 kg final RQ
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs**

• Propane, 1,2-epoxy-	75-56-9	100 lb EPCRA RQ
• Furan	110-00-9	100 lb EPCRA RQ
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs**

• Propane, 1,2-epoxy-	75-56-9	10000 lb TPQ
• Furan	110-00-9	500 lb TPQ
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

• Propane, 1,2-epoxy-	75-56-9	0.1 % de minimis concentration
• Furan	110-00-9	0.1 % de minimis concentration
• Acetaldehyde	75-07-0	0.1 % de minimis concentration
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	1.0 % de minimis concentration (listed under Chemical Category N120, Diisocyanates)
• Cobalt	7440-48-4	0.1 % de minimis concentration
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed



• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	(total)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	(total)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	(total)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	waste number U124 (Ignitable waste)
• Acetaldehyde	75-07-0	waste number U001 (Ignitable waste)
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**United States - California****Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Propane, 1,2-epoxy-	75-56-9	carcinogen, initial date 10/1/88
• Furan	110-00-9	carcinogen, initial date 10/1/93
• Acetaldehyde	75-07-0	carcinogen, initial date 4/1/88
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	carcinogen, initial date 7/1/92 (powder)
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - California - Proposition 65 - Developmental Toxicity**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed

• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	90 µg/day NSRL (inhalation)
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Female**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Male**

• Propane, 1,2-epoxy-	75-56-9	Not Listed
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**United States - Pennsylvania****Labor****U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**

• Propane, 1,2-epoxy-	75-56-9	
• Furan	110-00-9	
• Acetaldehyde	75-07-0	
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	
• Cobalt	7440-48-4	
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

**U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances**

• Propane, 1,2-epoxy-	75-56-9	
• Furan	110-00-9	Not Listed
• Acetaldehyde	75-07-0	Not Listed
• Isocyanic acid, methylenedi-p-phenylene ester	101-68-8	Not Listed
• Cobalt	7440-48-4	Not Listed
• Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Not Listed

## 15.2 Chemical Safety Assessment

| No Chemical Safety Assessment has been carried out.

## 15.3 Other Information

| WARNING: This product contains a chemical known to the State of California to cause cancer.

## Section 16 - Other Information

<b>Last Revision Date</b>	17/October/2013
<b>Preparation Date</b>	18/October/2011
<b>Disclaimer/Statement of Liability</b>	The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

**Key to abbreviations**  
NDA = No Data Available